# CLX COMPACT TRACE DETECTOR



**Detects Explosives** 

THERMO-REDOX

TRACE DETECTION



CLX is the latest advanced trace detection system for military and home made explosives (including precursors) designed by Scintrex Trace Corp. The instrument can be used at security checkpoints with minimal training. If a threat is present or if it isn't, the security personnel are informed within seconds. It is built to withstand rough handling and tough environments. Samples are collected from contaminated surfaces with a high efficiency swab or with the use of a portable external vapor sampler.

- > Rapid, accurate and easy to read results
- > Lightweight and field-ready
- > No radioactive source

## **APPLICATIONS:**

- > Force Protection
- > Law Enforcement
- > Transportation
- > Critical Infrastructure
- > Customs and Borders
- > High Security Events
- > Royal and Diplomatic Protection
- > Embassies and Consulates

500M0008 - Spec. Sheet: CLX - Rev. A - 10.24.2020

# **CLX SPECIFICATIONS**



Built to withstand rough handling and tough environments, the CLX packs potent detection capability into a light-weight, durable thermoplastic housing. The handheld CLX analyzes both particulates and vapors in seconds, without the need for radioactive isotopes or carrier gases.

A global leader in explosives, chemical and narcotics detection, Scintrex Trace is Autoclear's Canadian-based trace detection division. Like Autoclear's flagship X-ray systems, these products deliver unsurpassed accuracy, speed and reliability for detecting the most dangerous and cleverly concealed threats.

#### **SPECIFICATIONS**

Detector: Chemilux - MOS

Analysis Time: <10 seconds

EXPLOSIVES Detected: AN, NG, HMX, RDX, TNT, TETRYL, ETN,

R-SALT, C4, SEMTEX, TATP, HMTD, HNS, CL-20

UN, ANFO,

Detectable Precursors: Nitric acid, Perchlorate and

chlorate, Sulfur, Hydrogen Peroxide,

Picric Acid, Firecracker

Sensitivity: Particulates: low nanogram

Vapors: <10 parts-per-billion (external sampler)

Sample Collection: Particulates and vapors

Display: LCD 4.3"; sunlight-readable

Alarms: Visual, audible and vibration

Power Supply: External and built-in

Input Voltage: 14.4 V Li-ion

Unit Weight: 1.9 kg (4.2 lbs.) with battery

Unit Dimensions: 25.0 x 17.0 x 8.0 cm (L x W x H)

 $9.8 \times 6.7 \times 3.2 \text{ in.}$ 

Shipping Weight: TBD

Shipping Dimensions: TBD

Communication: USB, Ethernet and Wifi

Data Storage: More than 1,000 retrievable data records

IP Rating: IP54



### **Security Pro USA**

8543 Venice Blvd., Los Angeles, CA 90034, United States

Tel. 800.264.8273